



SmartBright G3 LED Floodlight

BVP151 LED240/CW PSU 200W SWB G3 GM

SmartBright G3 LED Floodlight, 24000 lm, 200 W, 865 cool daylight, 110°, Safety class I, Mounting bracket

The SmartBright G3 LED Floodlight is the new successor with robust die-cast aluminum housing suitable for general outdoor application. It delivers high efficacy and outstanding energy savings.

Product data

General Information		Effective projected area	
Number of gear units	1 unit		0.112 m ²
Gear	-	Operating and Electrical	
Driver included	Yes	Input Voltage	220 to 240 V
Light source engine type	LED	Line Frequency	50 or 60 Hz
Warranty period	3 years	Inrush current	4.38 A
		Inrush time	0.0284 ms
		Power Consumption	200 W
		Power Factor (Fraction)	0.95
		Connection	Flying leads/wires
		Cable	Cable 1.0 m without plug 3-pole
		Number of products on MCB of 16 A type B	11
		Suitable for random switching	Not applicable
		Protection class IEC	Safety class I
Light Technical		Controls and Dimming	
Luminous Flux	24,000 lm	Dimmable	No
Correlated Color Temperature (Nom)	6500 K	Control interface	-
Luminous Efficacy (rated) (Nom)	120 lm/W		
Color rendering index (CRI)	80		
Number of light sources	1		
Beam angle of light source	110 degree(s)		
Light source color	865 cool daylight		
Optic type	Wide beam		
Luminaire light beam spread	110°		

SmartBright G3 LED Floodlight

Maximum dim level	Not applicable
Mechanical and Housing	
Housing Material	Aluminum die-cast
Reflector material	Polycarbonate
Optic material	Glass
Optical cover material	Tempered glass
Housing Color	Grey
Mounting device	Mounting bracket
Optical cover finish	Clear
Overall length	474 mm
Overall width	336 mm
Overall height	37 mm
Dimensions (Height x Width x Depth)	37 x 336 x 474 mm
Ingress protection code	IP65 [Dust penetration-protected, jet-proof]
Mech. impact protection code	IK08 [5 J vandal-protected]
Optical cover type	Glass
Net Weight (Piece)	4.660 kg
Approval and Application	
Glow-wire test	Temperature 650 °C, duration 30 s
Flammability mark	For mounting on normally flammable surfaces
CE mark	No
ENEC mark	-

Photobiological risk	Photobiological risk group 1 @200mm to EN62778
Photobiological risk specification	0.2 m
EU RoHS compliant	Yes
Performance ambient temperature Tq	25 °C
Ambient temperature range	-25 to +40 °C
Initial Performance (IEC Compliant)	
Luminous flux tolerance	+/-10%
Initial chromaticity	(0.31, 0.34) SDCM≤5
Power consumption tolerance	+/-10%

Product Data

Order product name	BVP151 LED240/CW PSU 200W SWB G3 GM
Full product name	BVP151 LED240/CW PSU 200W SWB G3 GM
Full product code	872016973245299
Order code	911401868286
Material Nr. (12NC)	911401868286
Numerator - Quantity Per Pack	1
EAN/UPC - Product/Case	8720169732452
Numerator - Packs per outer box	4
EAN/UPC - Case	8720169732537

Dimensional drawing

